



### KEY FEATURES

- Adjustable length
- Suitable for Tank with small hole (up to 29mm)
- Connection for purge pipe 4X6 (return inside tank)
- Low level switch included and 2mt cable fully protected
- Integrated Non-return valve
- Easy maintenance
- With instruction kit
- 2 fixing ways (with 1" nut or with special seal)
- Flow rate up to 100 lt/h
- Max working temperature 50°C



		MATERIAL	
Body Ball Valves: Seals/O-rings		Standard Version	Upon request
		PP-PVC-NBR	
		Glass Pyrex Viton	PTFE Dutral

## ADLASNXXXX

1 LENGTH		2 MATERIALS		3 LEVEL PROBE		4 CONNECTION	
D	WAREWASHING	O	GL-VT	O	WITH LEVEL PROBE / WITHOUT CONNECTOR	0	4 X 6
0	T-A TANK 25L	A	GL-DT	C	WITH LEVEL PROBE / WITH CONNECTOR	1	10 X 14
1	T-A TANK 60/100L	B	PTFE-VT	N	WITHOUT LEVEL PROBE		
3	T-A TANK 2/300L	C	PTFE-DT				
5	T-A TANK 500L	S	NO VALVE				

Total length (B)	Suitable for A-TANK	A (Adjustable)
H400 mm	25L	115 mm → 300 mm
H700 mm	ADTANK006 – ADTANK010	115 mm → 600 mm
H940 mm	ADTANK020 – ADTANK030	115 mm → 840 mm

