

# SEALING SEALING

## LIQUID PVC ALKOR

Liquid PVC adhesive compound used for reinforcement of welding joints, internal and external corners of Renolit Alkorplan waterproofing membranes



## **Technical features**

- Polyvinyl chloride (PVC) and tetrahydrofuran (THF) solution in 1kg container
- Colours in blue, light blue, green, white, clear, black, sand, grey and dark grey
- A highly viscous fluid that has a thick, sticky consistency
- A volatile solvent that easily evaporates at normal temperature
- Low flash point: -17° Closed cup
- Consumption: approx. 1kg/100m



## Q Models

DESCRIPTION
Liquid PVC Applicator Bottle
Liquid PVC light blue adriatico
Liquid PVC blue
Liquid PVC light green caraibi
Liquid PVC white

PRODUCT CODE	DESCRIPTION
800800054	Liquid PVC transparent
800800064	Liquid PVC black
800800065	Liquid PVC sand
800800066	Liquid PVC gray
800800067	Liquid PVC dark gray

## LIQUID PVC ELBTAL

Liquid PVC for sealing and finishing of Elbtal PVC lining welds



## **Technical features**

- Polyvinyl chloride (PVC) and tetrahydrofuran (THF) solution in 1kg container
- Colours in blue, light blue, green, white, clear, black, sand, grey and dark grey
- A highly viscous fluid that has a thick, sticky consistency

- Low flash point: -17° Closed cupConsumption: approx. 1kg/100m
- PVC Liquido per liner ELBTAL



PRODUCT CODE	DESCRIPTION
800800049E	Liquid PVC Applicator Bottle
800800061E	Liquid PVC light blue adriatico
800800062E	Liquid PVC blue
800800063E	Liquid PVC light green caraibi
800800053E	Liquid PVC white
800800054E	Liquid PVC transparent
800800064E	Liquid PVC black
800800065E	Liquid PVC sand

DESCRIPTION
Liquid PVC gray
Liquid PVC dark gray
Liquid PVC Bali
Liquid PVC Bali / Capri / Hawai
Thairi
White artic
Sand beach
Deap Sea
Blue sky



# SEALING SEALING

## EPOXY ENAMEL



## **Technical features**

 Used for the waterproofing of pools or concrete basins in new or previously painted pools. Our 5kg epoxy enamel package is ideal as a catalyst (808800012), applying three coats is recommended.

## Application:

- 1. Remove dust, preferably with a vacuum cleaner
- 2. Clean with an acidic detergent, eliminating all traces of grease, rust, etc.
- 3. Rinse with water
- 4. Add the catalyst (not included) in a proportion of 1 to 2
- 5. Mix well and allow to settle for 15 minutes. Apply within 8 hours. The product can be applied with brush, roller or sprayed. If necessary, add nitro thinner
- 6. Wait 6-7 days before filling the pool



Coverage/mixing suggestions:

For first coat, use slightly diluted. Use 1kg of product for every 4 to 6 sq.m

For second coat, use undiluted. Use 1kg of product for every 4 to 6 sq.



## **Product**

PRODUCT CODE	DESCRIPTION
808800012	Catalyst for Enamel - 2.5kg
808800013	Epoxy Enamel - 5ka

## LINING GLUE



## **Technical features**

- ALKOR PLUS B40 is a solvent-based polyurethane adhesive that can be used for gluing flexible materials of synthetic origin (including plasticized materials)
- ALKOR PLUS B40 is used to facilitate hot-welding operations in the following cases:
  - o To glue the central part of the non-slip lining to ladders, steps and roman steps; the edge is then welded with Leister and sealed in the normal way
  - To pre-fasten the lining on reinforced concrete surfaces (for instance on steps, to ensure better traction for floor lining and on shutter housing top areas, without using anchor bolts)
  - o Installation of PVC lining over an existing PVC lining (for instance in case of repairs or reconstruction over old PVC lining, re-lining after installation of Foam layer); the perimeter of the new lining is then welded with Leister and sealed as usual



## Q Product

PRODUCT CODE	DESCRIPTION
800800072	Alkorplus Glue 5kg
800800014	R40 Glue 15kg





## 

42018 San Martino in Rio, Reggio Emilia Italy - Via Crotti, 1 P: +39 0522 695805/85 - F +39 0522 646160 aqua@aqua.it | www.aqua.it



## **Branches**

Unit 135 Oak Drive Hartlebury Trading Estate, Worcestershire, DY10 4JB P:+44 (0)1299 251050, F:+44 (0)1299 253704 sales@askaqua.co.uk | www.askaqua.co.uk

**AQUA FILTRACION S.A.**Pol. Ind. Castellbisbal Sud 08755
Castellbisbal, Barcelona

AQUA SU ARITIMI SAN. VE MUH. TIC. LTD. STI.
Ferhatpasa Mahallesi Maresal Fevzi Cakmak
Cad. No:45 Pk.34888 Atasehir / Istanbul - Turkey
P: +90 216 661 60 60, F: +90 216 661 68 50
info@aqua.com.tr | www.aqua.com.tr



AQUA GROUP LLC
Office: Regus – Sarayat EL Maadi, Egypt
Management & Warehouse: Plot no 2-2nd service
axe, 2nd Industrial Zone, October, Egypt
P: +20 2 3820 2259 | info@aqua.eg