

TEMPERATURE CONTROL 14/15

AIR COOLED WATER CHILLER-60Hz



✓ Technical features

- Touchscreen LCD control display - Can easily connect with a BMS
- Clock and timer on/off function
- Phase monitor: Protects the compressor in case of phase loss or inversion
- High/low pressure protection available
- cooled water temperature

🔍 Models

	R410a	CHU2-0110-60HZ	CHU2-0120-60HZ	CHU2-0130-60HZ	CHU2-0140-60HZ
Operating air temperature		10 °C~53 °C			
Operating water temperature		Cooling 7 °C~35 °C			
Functional selection		Cooling water			
Power Supply	V/PH/Hz	220/1/50		380~415/3/50	
Tank volume (Thermal insulation)	m3	1	1.5	2	2
	gallon	264	396	528	528
Performance condition		Air35 °C / Water inlet 45 °C~ 25 °C			
Cooling Capacity	kw	5.4	7.2	11.8	15.9
	BTU/H	18425	24566	40125	54264
Chilled water production ΔT=20°C	US Gal/h	1.8	2.5	4.5	6.1
Power Input	kw	8.4	11.7	8.1	10.9
Current	A	2.97	2.85	2.60	2.60
EER	W/W	2.94	2.85	2.83	2.83
Performance condition		Air46 °C / Water inlet 45 °C~ 25 °C			
Cooling Capacity	kw	4.6	6.1	10.0	13.5
Chilled water production ΔT=20°C	US Gal/h	2.2	3.0	5.3	7.2
Power Input	kw	10.0	13.8	9.5	12.9
Current	A	2.12	2.05	1.87	1.87
EER	W/W	2.12	2.05	2.04	2.04
Performance condition		Air46 °C / Humidity 80% / Water inlet 35 °C~ 10 °C			
Heating Capacity	kw	3.1	4.2	6.9	9.3
Chilled water production ΔT=40°C	US Gal/h	2.0	2.9	5.3	7.1
Power Input	kw	9.4	13.6	9.4	12.7
Current	A	1.54	1.44	1.31	1.31
EER	W/W	4.41	4.28	4.25	4.25
MAX.POWER INPUT	kW	2.4	3.5	6.3	8.5
MAX.CURRENT	A	11.3	16.3	11.3	15.3
Compressor Type		Rotary x 1	Rotary x 1	Scroll x 1	Scroll x 1
Controller		LCD			
Sound pressure level 1/3/5/10m	dB(A)	52/45/41/35	52/45/41/35	55/48/44/38	55/48/44/38
type		Titanium			
Standard water flow	m3/h	2.3	3.1	5.1	6.8
Standard water flow (min)	US GPM	1.1	8	2.5	3.4
Standard water flow (max)	US GPM	4.6	1.6	10.1	13.7
Water pressure drop (max)	kPa	6	6.3	11	13
Water connection	mm	threaded / 50	threaded / 50	threaded / 50	threaded / 50
Net	mm	1020 x 440 x 673	1020 x 440 x 673	1100 x 440 x 673	1100 x 440 x 873
Weight	kg	79/94	88/103	103/118	118/137



Models (Cont'd)

		CHU2-0150-60HZ	CHU2-0160-60HZ	CHU2-0170-60HZ	CHU2-0180-60HZ
Operating air temperature		10 °C~53 °C			
Operating water temperature		Cooling 7 °C~35 °C			
Functional selection		Cooling water			
Power Supply	V/PH/Hz	380~415/3/50	380~415/3/50	380~415/3/50	380~415/3/50
Tank volume (Thermal insulation)	m3	3.5	4	5	7
	gallon	925	1057	1321	1849
Performance condition		Air35 °C / Water inlet 45 °C~ 25 °C			
Cooling Capacity	kw	19.6	24.3	31	38
	BTU/H	66875	82925	107000	129929
Chilled water production ΔT=20°C	US Gal/h	7.6	9.4	12.2	14.8
Power Input	kw	13.5	16.8	21.8	26.5
Current	A	2.59	2.59	2.57	2.57
EER	W/W	2.82	2.82	2.80	2.80
Performance condition		Air46 °C / Water inlet 45 °C~ 25 °C			
Cooling Capacity	kw	16.7	20.7	26.7	32.4
Chilled water production ΔT=20°C	US Gal/h	8.9	11.1	14.4	17.5
Power Input	kw	16.0	19.8	25.7	31.2
Current	A	1.86	1.86	1.85	1.85
EER	W/W	2.03	2.03	2.02	2.02
Performance condition		Air46 °C / Humidity 80% / Water inlet 35 °C~ 10 °C			
Heating Capacity	kw	11.5	14.3	18.4	22.3
Chilled water production ΔT=40°C	US Gal/h	8.8	10.9	14.2	17.2
Power Input	kw	15.7	19.5	25.4	30.8
Current	A	1.30	1.30	1.30	1.30
EER	W/W	4.23	4.23	4.20	4.20
MAX.POWER INPUT	kW	10.6	13.1	17.0	20.7
MAX.CURRENT	A	18.9	23.4	30.4	36.9
Compressor Type		Scroll x 1	Scroll x	Scroll x 2	Scroll x 2
Controller		LCD			
Sound pressure level 1/3/5/10m	dB(A)	58/51/47/41	58/51/47/42	59/53/49/44	59/53/49/44
type		Titanium			
Standard water flow	m3/h	8.4	10.5	13.5	16.4
Standard water flow (min)	US GPM	4.2	5.2	6.7	24
Standard water flow (max)	US GPM	16.9	20.9	27.0	8.2
Water pressure drop (max)	kPa	16	20	22	32.7
Water connection	mm	threaded / 50	threaded / 63	threaded / 63	threaded / 63
Net	mm	1150 x 450 x 973	1100 x 440 x 1378	1454 x 755 x 1705	1454 x 755 x 1705
Weight	kg	129/150	194/207	290/323	317/350



Your global partner since 1974. Trusted for superior quality and exceptional innovations.



Head Office

AQUA S.p.A

42018 San Martino in Rio, Reggio Emilia
Italy - Via Crotti, 1
P: +39 0522 695805/85 - F: +39 0522 646160
aqua@aqua.it | www.aqua.it



Branches

AQUA WATER SYSTEMS LTD

Unit 135 Oak Drive Hartlebury Trading Estate,
Worcestershire, DY10 4JB
P: +44 (0)1299 251050, F: +44 (0)1299 253704
sales@askaqua.co.uk | www.askaqua.co.uk

AQUA FILTRACION S.A.

Pol. Ind. Castellbisbal Sud 08755
Castellbisbal, Barcelona
P: +34 (0)93 7711855, F: +34 (0)93 7711772
info@aqua.es | www.aqua.es

AQUA SU ARITIMI SAN. VE MUH. TIC. LTD. STI.

Ferhatpasa Mahallesi Maresal Fevzi Cakmak
Cad. No:45 Pk.34888 Atasehir / Istanbul - Turkey
P: +90 216 661 60 60, F: +90 216 661 68 50
info@aqua.com.tr | www.aqua.com.tr

AQUA S.p.A - POOL DIVISION

46043 Castiglione d. Stiviere, Mantova - Italy
P: +39 0376 671973 - F: +39 0376 940139
infopools@aqua.it | www.aqua.it

AQUA MIDDLE EAST FZC

1J-07/4 and 1J-07/3 - Hamriyah Free Zone
P.O.Box 42585 Sharjah - United Arab Emirates
P: +971 6 526 0563, F: +971 6 526 0564
contact@aqua-me.ae
www.aqua-me.ae

AQUA WATER SYSTEMS INDIA PVT LTD

4A/4B/4C-, Puttappa Industrial Estate
Mahadevapura Post, White Field Road,
Bangalore 560 048
P: 0091 80 4152 1313, F: 0091 80 4152 1414
contact@aquaindia.in | sales@aquaindia.in
www.aquaindia.in



AQUA GROUP RUS

Juridical Address:
107014, Egerskaya str, 1, Moscow, Russia
Residence Address:
127081, Chermianskaya str, 3, Moscow, Russia
P: +7 495 6458078, F: +7 495 969 2413
mail@aqua-italy.ru | www.aqua-italy.ru
www.aqua.it

AQUA GROUP LLC

Office : Regus - Sarayat EL Maadi, Egypt
Management & Warehouse : Plot no 2-2nd service
axe, 2nd Industrial Zone, October, Egypt
P: +20 2 3820 2259 | info@aqua.eg